

Get the results you need in your heating process...



...power to 300kW
...operation from 15kHz to 45kHz

World-class Induction Heating Systems

Versatile

- efficient heating of many part geometries, sizes and compositions
 - multiple capacitor configurations
 - multiple tap transformer configurations
- repeatable, reliable heating with agile frequency tuning
- through-Curie heating
- movable work head; up to 30m(100')
- sub-second to continuous cycle times
- remote operation or logging with RS485 port
- accepts international AC line voltages

Easy to Use

- user-friendly operator front panel controls
- system configuration from front panel
- cycle timer, peak and short-cycle data capture
- 10 ten-step heating profiles
- overload-tolerant output management
- 5-language display suite (EN, ES, FR, DE, IT)

EKOHEAT induction heating systems for 15-45 kHz range provide reliable and repeatable solutions for heating larger parts when efficient heating of your part dimensions requires higher frequencies than our 10kHz models. Among the many typical applications are heat treating of steels, preheating for forging of steel, aluminum, copper or brass, crystal growing, and heating of graphite and metal crucibles.

EKOHEAT is CE marked and manufactured at our ISO 9001:2008 certified facility
Model shown with optional accessories



10
9
6
4.2 kW
150-400 kHz
2.4
1.2 kW
150-400 kHz
270
225
180 kW
50-150 kHz
135
90
65 kW
50-150 kHz
45
30 kW
50-150 kHz
15
10 kW
50-150 kHz

300
200 kW
15-45 kHz

75 kW
15-45 kHz
50
35 kW
15-45 kHz
250
125
100
75 kW
5-15 kHz
50
35 kW
5-15 kHz

With the versatile EKOHEAT power control system you get rapid tuning, efficient and precise heating of your parts, power control within 0.2% resolution and an easy-to-use, easy-to-read front panel. Remote control is accomplished with 0-10V, 4-20mA inputs, RS485 serial port, 24V controls and remote E-Stop input so integration with your automated production lines is easy.

EKOHEAT technology improves return on investment by reducing

your energy usage compared to gas-fired and resistive heating techniques. Flameless, non-contact induction heating minimizes energy waste by focusing energy only on the part and zone to be heated. With very efficient power conversion and a power factor greater than 0.9, your utility demand charges are reduced, lowering your monthly energy bills. EKOHEAT systems are designed for efficient use of cooling water, further lowering your operating costs.

Automatic tap changer, multiple work head controller, pendant stations, heat exchangers, data logging and other options and accessories are available for a wide variety of applications.

This is a water-cooled system, requiring connection to a heat exchanger or other means of dissipating heat.

Specification	200/30	300/30	units
RF Terminal Power (continuous)	200	300	kW
AC Line Power	234	349	kVA
Power Factor	0.92		
Output Frequency	15-45		kHz
AC Line Voltage	360 – 520		Vac, 3Ø
AC Line Protection ¹	400	600	A
Display	LCD monochrome, 240w x 128h pixels		
Serial Communication	RS485 standard (RS485/232 converter optional)		
Process Timer	0.01 - 10000		sec
Max Ambient Temp	45 (115)		°C(°F)
Compliance	CE		
Ingress Protection	IP54, NEMA 12		
Dimensions	1718x806x1906 (67x32x75)		WxDxH mm(in)
Weight	395(865)	452(995)	kg (lb)

Water Cooling

Flow ²	38(10)	57(15)	l/m (g/m)
Pressure Differential (range)	2.8 – 5.6 (40 – 80)		bar (lb/in ²)
Max Water Temp	35 (95)		°C(°F)

- 1) fast-acting fuses
- 2) power supply; required workhead coil flow requirements vary by application



Options and Accessories

- ✓ start-up assistance
- ✓ heat exchanger or chiller
- ✓ pendant station
- ✓ autotap selection
- ✓ redundant safety relays
- ✓ multi workhead controller
- ✓ eVIEW serial data reporting
- ✓ footswitch
- ✓ extended work head cable lengths
- ✓ optical pyrometer (closed-loop temperature control)
- ✓ external controller (plc)
- ✓ front E-stop with retransmission



EKOHEAT features a front panel programmable controller for monitoring, timer & power-level control, diagnostics and system configuration. Up to 10 ten-step heating profiles can be configured to control power levels over your specified timing requirements.



Visit our extensive library of Application Notes at www.ameritherm.com/appnotes.php